

Safety Data Sheet

SENERLASTIC PLUS COATING COLOR

Revision date : 2009/12/02
Version: 1.0

Page: 1/5
(30418944/SDS_GEN_CA/EN)

1. Product and Company Identification

Company
BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

24 Hour Emergency Response Information
CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE: (800) 454-COPE (2673)

2. Hazards Identification

Emergency overview

Contains a carcinogen.

State of matter: liquid
Colour: opaque
Odour: ammonia-like

Potential health effects

Chronic toxicity:

Carcinogenicity: IARC has determined that there is sufficient evidence of carcinogenicity in both humans and experimental animals for inhaled crystalline silica in the form of quartz or cristobalite.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Hazardous ingredients</u>
14808-60-7	>= 0.1 - <= 1.0 %	crystalline silica

4. First-Aid Measures

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention.

If on skin:
Remove contaminated clothing. Wash thoroughly with soap and water. If symptoms persist, seek medical advice.

Safety Data Sheet

SENERLASTIC PLUS COATING COLOR

Revision date : 2009/12/02
Version: 1.0

Page: 2/5
(30418944/SDS_GEN_CA/EN)

If in eyes:

Flush with copious amounts of water for at least 15 minutes. If symptoms persist, seek medical advice.

If swallowed:

Do not induce vomiting unless told to by a poison control center or doctor. If person is conscious and can swallow, give two glasses of water.

5. Fire-Fighting Measures

Flash point: 93.34 °C
Lower explosion limit: No data available.
Upper explosion limit: No data available.

Suitable extinguishing media:

carbon dioxide, dry extinguishing media, foam, water fog, water spray

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Sealed containers should be protected against heat as this results in pressure build-up. Keep containers cool by spraying with water if exposed to fire.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Avoid contact with the skin, eyes and clothing.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

Dike spillage. Vacuum up spilled product. Pick up with inert absorbent material (if possible). Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Handling

General advice:

Ensure thorough ventilation of stores and work areas.

Storage

General advice:

Keep container tightly closed and dry; store in a cool place.

Temperature tolerance

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

8. Exposure Controls and Personal Protection

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Safety Data Sheet

SENERLASTIC PLUS COATING COLOR

Revision date : 2009/12/02
Version: 1.0

Page: 3/5
(30418944/SDS_GEN_CA/EN)

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection:

impermeable gloves

Eye protection:

Safety glasses with side-shields. Wear face shield if splashing hazard exists.

Body protection:

Impermeable protective clothing

General safety and hygiene measures:

Food, beverages, and tobacco products shall not be carried, stored, or consumed where this material is in use. Hands and/or face should be washed before breaks and at the end of the shift. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	ammonia-like	
Odour threshold:	No data available.	
Colour:	opaque	
pH value:	9.0 - 9.5	
:		No data available.
Boiling point:	100 °C	
Vapour pressure:		No data available.
Density:	approx. 1.0 g/cm ³	(20 °C)
Relative density:	1.38	
Vapour density:		No data available.
Partitioning coefficient n-octanol/water (log Pow):		No data available.
Viscosity, dynamic:		No data available.
% volatiles:		
Solubility in other solvents:		soluble

10. Stability and Reactivity

Substances to avoid:

No data available.

Hazardous reactions:

The product is chemically stable.

No hazardous reactions when stored and handled according to instructions.

Decomposition products:

carbon oxides, nitrogen oxides

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

11. Toxicological information

Acute toxicity

Oral:

Safety Data Sheet

SENERLASTIC PLUS COATING COLOR

Revision date : 2009/12/02
Version: 1.0

Page: 4/5
(30418944/SDS_GEN_CA/EN)

No data available.

Inhalation:

No data available.

Dermal:

No data available.

Repeated dose toxicity

Information on: ethyleneglycol

Carcinogenicity

Information on: crystalline silica
The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

12. Ecological Information

Other adverse effects:

Ecological data are not available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge substance/product into sewer system. Dispose of in accordance with local authority regulations.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Safety Data Sheet

SENERLASTIC PLUS COATING COLOR

Revision date : 2009/12/02
Version: 1.0

Page: 5/5
(30418944/SDS_GEN_CA/EN)

15. Regulatory Information

VOC content:
80 g/l

Federal Regulations

WHMIS classification: D2A: Materials Causing Other Toxic Effects - Very toxic material



THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

16. Other Information

BASF supports worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Local Contact Information
BASF Construction Chemicals
bcc_prps@basf.com

END OF DATA SHEET