

Safety Data Sheet

SENERQUICK ADHESIVE

Revision date : 2011/03/02

Version: 1.0

Page: 1/7

(30368377/SDS_GEN_US/EN)

1. Product and Company Identification

Use: Product for construction chemicals

Company

BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. Hazards Identification

Emergency overview

WARNING:

MAY CAUSE EYE IRRITATION.

MAY CAUSE SKIN IRRITATION.

Ingestion may cause irritation to mucous membranes.

CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Avoid contact with the skin, eyes and clothing.

Wash thoroughly after handling.

Keep container tightly closed.

Colour: white

Odour: ammonia-like, slight odour

Potential health effects

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

The product has not been tested. The statement has been derived from the properties of the individual components.

Irritation / corrosion:

Irritating to eyes, respiratory system and skin.

Sensitization:

There is no evidence of a skin-sensitizing potential.

Potential environmental effects

Aquatic toxicity:

The product has not been tested.

Safety Data Sheet

SENERQUICK ADHESIVE

Revision date : 2011/03/02
Version: 1.0

Page: 2/7
(30368377/SDS_GEN_US/EN)

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
1317-65-3	>= 30.0 - <= 60.0 %	Limestone
14808-60-7	>= 0.1 - <= 1.0 %	crystalline silica
64741-88-4	>= 0.1 - <= 1.0 %	Distillates (petroleum), solvent-refined heavy paraffinic
64741-89-5	>= 0.1 - <= 1.0 %	Distillates (petroleum), solvent-refined light paraffinic

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately with water. Seek medical attention if necessary. Do not induce vomiting unless told to by a poison control center or doctor.

5. Fire-Fighting Measures

Flash point:	93.34 °C	
Lower explosion limit:		No data available.
Upper explosion limit:		No data available.

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Handle in accordance with good building materials hygiene and safety practice.

Safety Data Sheet

SENERQUICK ADHESIVE

Revision date : 2011/03/02
Version: 1.0

Page: 3/7
(30368377/SDS_GEN_US/EN)

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Handling

General advice:

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Storage

General advice:

Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

Temperature tolerance

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 32 °F

The packed product must be protected from temperatures below the indicated one.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

crystalline silica	OSHA	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.1 mg/m3 Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.3 mg/m3 Total dust ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
Distillates (petroleum), solvent-refined heavy paraffinic	ACGIH OSHA ACGIH	TWA value 0.025 mg/m3 Respirable fraction ; PEL 500 ppm 2,000 mg/m3 ; PEL 5 mg/m3 Mist ; ; Included in the regulation, but with no data values - See the regulation for further details ; Exposure by all routes should be carefully controlled to levels as low as possible.
Distillates (petroleum),	OSHA	TWA value 5 mg/m3 Inhalable fraction ; PEL 5 mg/m3 Mist ;

Safety Data Sheet

SENERQUICK ADHESIVE

Revision date : 2011/03/02

Page: 4/7

Version: 1.0

(30368377/SDS_GEN_US/EN)

solvent-refined light paraffinic	ACGIH	;	Included in the regulation, but with no data values - See the regulation for further details
		;	Exposure by all routes should be carefully controlled to levels as low as possible.
Limestone	OSHA	TWA value 5 mg/m3 Inhalable fraction ;	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ;

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields.

Body protection:

depending upon conditions of use., Cover as much of the exposed skin as possible to prevent all skin contact., light protective clothing

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	ammonia-like, slight odour	
Colour:	white	
pH value:		slightly alkaline
Boiling point:	100 °C	
Density:	1.18 - 1.31 g/cm3	(20 °C)
Partitioning coefficient n-octanol/water (log Pow):		not applicable

10. Stability and Reactivity

Conditions to avoid:

Avoid extreme temperatures.

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

Safety Data Sheet

SENERQUICK ADHESIVE

Revision date : 2011/03/02
Version: 1.0

Page: 5/7
(30368377/SDS_GEN_US/EN)

No decomposition if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

11. Toxicological information

Carcinogenicity

Information on: crystalline silica

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

Information on: Distillates (petroleum), solvent-refined heavy paraffinic

The substance caused cancer in animal studies.

Information on: Distillates (petroleum), solvent-refined light paraffinic

The substance caused cancer in animal studies. Relating to this endpoint the product has not been fully tested.

The statement has been derived from the structure of the product.

Experiences in humans:

According to experience, the product is considered to be harmless to health if used in the correct manner.

Other Information:

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Other adverse effects:

The product has not been tested. Do not allow to enter soil, waterways or waste water channels.

13. Disposal considerations

Waste disposal of substance:

Recommendations: Use excess product in an alternate beneficial application. Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with local authority regulations.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Safety Data Sheet

SENERQUICK ADHESIVE

Revision date : 2011/03/02
Version: 1.0

Page: 6/7
(30368377/SDS_GEN_US/EN)

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

Registration status based on supplier confirmation

OSHA hazard category: IARC 1, 2A or 2B carcinogen; NTP listed carcinogen; Chronic target organ effects reported

EPCRA 311/312 (Hazard categories): Acute; Chronic

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	98-82-8; 71-36-3; 67-64-1; 64-19-7	cumene; n-butanol; Acetone; Acetic acid
1000 LBS	25155-30-0; 100-41-4; 80-62-6; 1336-21-6	sodium dodecylbenzenesulphonate, pure; ethylbenzene; Methyl methacrylate; Ammonium hydroxide
100 LBS	1330-20-7; 7664-41-7; 50-00-0; 142-96-1; 75-65-0	Xylene; ammonia; Formaldehyde; dibutyl ether; 2-methylpropan-2-ol

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	14808-60-7	crystalline silica
MA, NJ, PA	64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic
MA, NJ, PA	64741-89-5	Distillates (petroleum), solvent-refined light paraffinic

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

16. Other Information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

Safety Data Sheet

SENERQUICK ADHESIVE

Revision date : 2011/03/02

Page: 7/7

Version: 1.0

(30368377/SDS_GEN_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:

BASF NA Product Regulations

msds@basf.com

MSDS Prepared on: 2011/03/02

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET